

INTERCOM 1300

MICROPHONE INTERCOM SYSTEM



DESCRIPTION

Intercom system for counters:

Installed in different rooms the INTERCOM 1300 system allows users to speak and listen at each end without having to press any buttons. The kit is composed of three separate modules: control station, power supply and loudspeaker unit with integral microphone. The devices function in halfduplex (one-at-a-time) mode and activation thresholds are modified automatically in relation to environmental background noise levels. The operation station can enable one-way operation, i.e. exclusively automatic listening, with speak facility at the press of a button.

Optional accessories:

- Supplementary loudspeaker for operator station
- Headset with microphone for operator station

TECHNICAL DATA

Control microphone station	
Power supply	230Vac, 50Hz
Absorption	16VA
External microphone input	2mV unbalanced, 10kOhm / 5V
Connections	mini-jack 3,5mm
Dimensions / Weight	160 x 55 (410) x 205mm / 0,94kg
External loudspeaker	
Impedance	8 Ohm
Power	2W (4W peak)
Frequency response	200Hz ÷ 6.000Hz
Dimensions / Weight	115 x 55 x 65mm / 0,56kg
	Sensitivity -44dB
Omnidirectional microphone	Impedance 600 Ohm
	Frequency response 50Hz ÷ 15.000Hz
Power supply unit	
Power supply	230Vac, 50Hz
Maximum consumption	16VA
Voltage supplied	12V / 0,7A
Dimensions / Weight	160 x 80 x 110mm / 1,2kg